Model No.: RS-UW48W316X Model No.: RS-UW64W316X

Item Code: 88107

FEATURES

- -High efficiency light source, Cree & Edison 3W high power led.
- -High quality Stainless steel 316 lamp fixture/lamp, Beautiful appearance and reasonable waterproof structure.
- -Tempered glass as cover, heat-resisting and impact resistance.
- -Supplied with 1.5m 3wires/5wires VDE rubber cable or UL rubber cable.
- -Long life, up to 45,000 hours.
- -Waterproof IP68, outdoor use.
- -Beam angle10-90°.



OPTIONS ON REQUEST

- -Cable lengths can be supplied according to your requirements
- -Beam angle 10° 30° 45° 60° 90° for optional
- -316L or 316Ti is optional
- -RDM, DMX512 (3 channel), DMX512 (4 channel), Auto change color can be optional.

▶ SPECIFICATION

Body size D175 x H230mm (max.)

Output Power48W/64WLuminous Flux Output80-90LM/W

Rendering Index Ra>70

Lens surface Mirrored, Beaded, Striped


Light source EDISON or CREE


IP Grade IP68

Housing material Stainless steel 316

Cable gland PG13.5, Stainless steel 316

Control Mode Auto color change / DMX512 controllable







Model No.: RS-UW48W316X Model No.: RS-UW64W316X

Item Code: 88107

Order information

Item code	LED Q'ty	Color	Control Mode	Line Way	Working Voltage
88107.163.16	16pcs 3in1 LED (16R+16G+16B)		DMX512 (3 channel)	V+/V-/D+/D-	DC24V
88107.164.17	16pcs 4in1 LED (16R+16G+16B+16W)	RGBW	DMX512 (4 channel)	V+/V-/D+/D-	DC24V

Please contact us freely if you have any special requirements.

Accessories



93000023

T type IP68 quick connector suitable for 6.8-10mm **Ø** cables max. 3 x 2.5mm² or 5 x 2.5mm²



93000024

IP68 quick connector suitable for 6.8-10mm **Ø** cables max. 3 x 2.5mm²



93000025

IP68 quick connector suitable for 8-12mm **Ø** cables max. 5 x 2.5mm²



IP23 Switch Power Supply

Will be chosed according to the light quantity and cable length.



IP66 Switch Power Supply

Will be chosed according to the light quantity and cable length.



88612

DMX512 CONTROLLER Model No.: DMX500



88605

2. 4G wireless DMX/RDM signal converter Model No.:DSC-24



88606

DMX/RDM signal amplifier Model No.:DSA-01



12000011

Material: 316stainless steel Size: 240*87mm



88604

12 way DMX/RDM signal amplifier and power splitter Model No.: DSP-12



88607

DMX/RDM signal amplifier Model No.:DSA-01P IP68



12000010

Material: 316stainless steel Size: 92*4.5mm




Model No.: RS-UW48W316X Model No.: RS-UW64W316X

Item Code: 88107








The radiator

Adopting 316 stainless steel and thicken radiator, sufficient material to use, beautiful appearance, super performance for conductivity, perfect solution for the heat-dispersing of lamp body, keeping a very long lifespan for the light.



Opticallens

High quality 316 stainless steel helmet, superior level of tempered glass, resist eompression and crack, Super light transmiting ratio with advanced optical lens



Stents

High quality 316 stainless steel with adding thicken bracket, 100% sufficient material used, super power of hardness to protect the light from damaging, guaranteeing the light body to keep balance forever.



Screw

Adopting superior quality screw of 316 stainless steel, super strong for hardness, protecting the light from damaging, being able to resist rust permanently, to support and fix the lamp body powerfully.

Item Code: 88107 Model No.: RS-UW48W316X Model No.: RS-UW64W316X

